



Test Report : SBTN01L-12

1W SMD Package DC-DC Unregulated Converter

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

■ SAFETY TEST

Safety Test

■ RELIABILITY TEST

Environment Test

Other test

DESIGN VERIFY TEST

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	VOLTAGE ACCURACY	-2%~+2%	I/P:5VDC O/P:FULL LOAD Ta:25°C	+0.6%	P
2	RIPPLE & NOISE	75mVp-p (Max)	I/P:5VDC O/P:FULL LOAD Ta:25°C	45mVp-p	P
3	LINE REGULATION	-12% ~ +12% (Max)	I/P:4.5VDC ~5.5VDC O/P:FULL LOAD Ta:25°C	-11.03% ~ +11.20%	P
4	LOAD REGULATION	-8% ~ +8% (Max)	I/P:5VDCC O/P:FULL ~MIN LOAD Ta:25°C	-2.83% ~ +2.70%	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	EFFICIENCY	80%	I/P:5VDC O/P:FULL LOAD Ta:25°C	81.46%	P
2	DC CURRENT	257mA FULL LOAD 30mA NO LOAD	I/P:5VDC O/P:FULL LOAD Ta:25°C	248mA 28mA	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	SHORT PROTECTION	MOMENTARY	I/P:5.5VDC O/P:FULL LOAD Ta:25°C	MOMENTARY	P

SAFETY TEST

SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P:1.5KVDC/min	I/P-O/P:1.5KVDC/min Ta:25°C	I/P-O/P:0.02mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P:500VDC Ta:25°C	I/P-O/P:>100MΩ NO DAMAGE	P

RELIABILITY TEST
ENVIRONMENT TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT										
1	TEMPERATURE RISE TEST	1. ROOM AMBIENT BURN-IN : 4HRS I/P:5VDC O/P:100% LOAD Ta=25°C 2. HI AMBIENT BURN-IN : 10HRS I/P:5 VDC O/P:100% LOAD Ta=85°C			P										
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>P/N</th> <th>1</th> <th>2</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>CASE</td> <td>CENTER</td> <td>36.4°C</td> <td>94.9°C</td> </tr> </tbody> </table>		NO	Position	P/N	1	2	1	CASE	CENTER	36.4°C	94.9°C		
NO	Position	P/N	1	2											
1	CASE	CENTER	36.4°C	94.9°C											
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOURS	I/P : 5VDC O/P : 100% LOAD Ta= -40°C	TEST : OK	P										

OTHER

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	MTBF	MIL-KDBK-217F NOTICES 2 PARTS COUNT TOTAL FAILURE RATE : 1.13390 M.T.B.F : 881914.32 HRS			P

TEST RESULT	TESTER	APPROVAL
PASS	ARCHEN	VINCENT ZENG