

Model : SCW08B-15 8W  
+15V / 533mA

**OUTPUT FUNCTION TEST**

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	OUTPUT VOLTAGE ACCURACY	-2%~+2%	I/P: 24VDC O/P:50% LOAD Ta:25°C	0.52%	P
2	RIPPLE & NOISE	60mVp-p	I/P:24VDC O/P:FULL LOAD Ta:25°C	27.2mVp-p	P
3	LINE REGULATION	-0.5%~+0.5%	I/P:18VDC ~36VDC O/P:FULL LOAD Ta:25°C	-0.01%~+0.01%	P
4	LOAD REGULATION	-0.5%~+0.5%	I/P:24VDC O/P: MIN ~FULL LOAD Ta:25°C	-0.03%~+0.02%	P

**INPUT FUNCTION TEST**

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	18VDC~36VDC	I/P:TESTING O/P:FULL LOAD Ta:25°C	14.5V~36Vdc	P
2	EFFICIENCY	81% (Typ)	I/P:24VDC O/P:FULL LOAD Ta:25°C	86.5%	P
3	INPUT CURRENT	426mA FULL LOAD (Max.) 25mA NO LOAD (Typ.)	I/P:24VDC O/P:TEST Ta:25°C	383mA / FULL LOAD 13mA / NO LOAD	P

**PROTECTION FUNCTION TEST**

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	110%~180%(Typ)	I/P:24VDC O/P:TESTING Ta:25°C	167% HICCUP MODE AUTO-RECOVER	P
2	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P:36VDC O/P:FULL LOAD Ta:25°C	NO DAMAGE HICCUP MODE AUTO-RECOVER	P



## ENVIRONMENT TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT					
1	TEMPERATURE RISE TEST	1. ROOM AMBIENT BURN-IN : 3HRS I/P:24VDC O/P: FULL LOAD Ta= 24.5°C			P					
		<table border="1"> <thead> <tr> <th>Position</th> <th>P/N</th> <th>1</th> </tr> </thead> <tbody> <tr> <td>CASE</td> <td>CENTER</td> <td>45.4°C</td> </tr> </tbody> </table>				Position	P/N	1	CASE	CENTER
Position	P/N	1								
CASE	CENTER	45.4°C								

## SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P:1500 VDC/min	I/P-O/P:1500 VDC/min Ta:25°C	I/P-O/P: 0.02mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P:500 VDC Ta:25°C	I/P-O/P>100MΩ NO DAMAGE	P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2022.3.9	STOCK	PASS	PETER	T.K.CHENG