

Quality Engineering Test Report

SERIES: SD-50C 50W DC-DC SINGLE OUTPUT SWITCHING POWER SUPPLY

SAMPLE: **A. SD-50C-5 5V / 10A**
 B. SD-50C-12 12V / 4.2A
 C. SD-50C-24 24V / 2.1A

NO	TEST ITEM	TEST CONDITION / SPECIFICATION	RESULT	VERDICT
1	DC INPUT VOLTAGE RANGE	I/P : TESTING SPEC : 36~72VDC O/P : FULL LOAD	A:27.9~72VDC	P
2	LINE REGULATION	I/P : 36~72VDC SPEC : A:±0.5% O/P : FULL LOAD B:±0.3% C:±0.2%	A:-0%~+0% B:-0%~+0% C:-0%~+0%	P
3	LOAD REGULATION	I/P : 48VDC SPEC : A:±0.5% O/P : MIN. TO FULL LOAD B:±0.3% C:±0.2%	A:-0.12%~+0.24% B: -0%~+0.05% C:-0.02%~+0.02%	P
4	OUTPUT VOLTAGE TOLERANCE	I/P : 36~72VDC SPEC : A:±2% O/P : MIN. TO FULL LOAD B:±1% C:±1%	A:-0.12%~+0.24% B: -0%~+0.1% C:-0.02%~+0.02%	P
5	RIPPLE&NOISE	I/P : 48VDC SPEC : A:100mVp-p O/P : FULL LOAD B:120mVp-p C:150mVp-p	A:12mV B: 3mV C: 8mV	P
6	DC INPUT CURRENT	I/P : 48VDC SPEC : 1.5A O/P : FULL LOAD	A:1.268A	P
7	MAX. INRUSH CURRENT	I/P : 48VDC SPEC : NONE O/P : FULL LOAD	A:54.3A	P
8	O/P VOLTAGE ADJ. RANGE	I/P : 48VDC SPEC : A:4.5~5.5V O/P : MIN. LOAD B:11~16V C:23~30V	A:4.40~6.21V B:9.62~16.34V C:19.6~33.40V	P
9	SET UP TIME	I/P : 48VDC SPEC : 2.5S O/P : FULL LOAD	A:2211.4mS	P
10	EFFICIENCY	I/P : 48VDC SPEC : A:76% O/P : FULL LOAD B:78% C:83%	A:81.07% B:83.1% C:86.19%	P
11	OVER LOAD PROTECTION	I/P : 48VDC SPEC : 105%~150% O/P : TESTING	A:130% B:133.5% C:138.5%	P
12	OVER VOLTAGE PROTECTION	I/P : 48VDC SPEC : A:5.75V~6.75V O/P : TESTING B:16.8V~20V C:31.5V~37.5V	A:6.22V B:17.98V C:35.40V	P
13	INSULATION RESISTANCE	SPEC : I/P-O/P 500VDC/100M Ohms MIN. I/P-FG 500VDC/100M Ohms MIN. O/P-FG 500VDC/100M Ohms MIN.	A: I/P-O/P : >100M Ohms I/P-FG : >100M Ohms O/P-FG : >100M Ohms	P
14	DIELECTRIC / WITHSTAND VOLTAGE	SPEC : I/P- O/P : 1500VAC/ 1 min (10mA CUT-OFF) I/P- FG : 1500VAC/ 1 min (10mA CUT-OFF) O/P- FG : 500VAC/ 1 min (10mA CUT-OFF)	A: I/P-O/P : <2.1mA I/P-FG : <2.32mA O/P-FG : <2.38mA	P

15	BURN-IN TEST	I/P : 48VDC TA : 23.9 °C	O/P:FULL LOAD BURN-IN DURATION : 3 hrs	NON BREAK	P
16	ENVIRONMENT TEST (SAMPLE A:)	HIGH AMBIENT TEMPERATURE FULL LOAD TEST I/P : 48VDC AMBIENT TEMPERATURE : 53.4°C	O/P : FULL LOAD	AFTER 13 hrs NON BREAK	P

NO	TEST ITEM	TEST CONDITION / SPECIFICATION	RESULT	VERDICT																												
17	TEMPERATURE RISE TEST T rise OF PARTS	<p>A: I/P : 48VDC AFTER 2 hr BURN-IN O/P : FULL LOAD TA : 23.9°C</p> <table border="1"> <thead> <tr> <th>POSITION</th> <th>P/N</th> <th>TEMP</th> <th>T rise</th> </tr> </thead> <tbody> <tr> <td>Q1</td> <td>MAIN TRANSISTOR</td> <td>49.3°C</td> <td>25.4°C</td> </tr> <tr> <td>T1</td> <td>MAIN TRANSFORMER</td> <td>66.3°C</td> <td>42.4°C</td> </tr> <tr> <td>D11</td> <td>O/P DIODE</td> <td>62.1°C</td> <td>38.2°C</td> </tr> <tr> <td>C34</td> <td>O/P FILTER CAPACITOR</td> <td>51.4°C</td> <td>27.5°C</td> </tr> <tr> <td>L1</td> <td>O/P CHOCK</td> <td>63.8°C</td> <td>39.9°C</td> </tr> <tr> <td>C5</td> <td>I/P FILTER CAPACITOR</td> <td>43.4°C</td> <td>19.5°C</td> </tr> </tbody> </table>	POSITION	P/N	TEMP	T rise	Q1	MAIN TRANSISTOR	49.3°C	25.4°C	T1	MAIN TRANSFORMER	66.3°C	42.4°C	D11	O/P DIODE	62.1°C	38.2°C	C34	O/P FILTER CAPACITOR	51.4°C	27.5°C	L1	O/P CHOCK	63.8°C	39.9°C	C5	I/P FILTER CAPACITOR	43.4°C	19.5°C		P
POSITION	P/N	TEMP	T rise																													
Q1	MAIN TRANSISTOR	49.3°C	25.4°C																													
T1	MAIN TRANSFORMER	66.3°C	42.4°C																													
D11	O/P DIODE	62.1°C	38.2°C																													
C34	O/P FILTER CAPACITOR	51.4°C	27.5°C																													
L1	O/P CHOCK	63.8°C	39.9°C																													
C5	I/P FILTER CAPACITOR	43.4°C	19.5°C																													
18	LIFE CYCLE	<p>A: SUPPOSE C34 IS THE MOST CRITICAL COMPONENT I/P : 48VDC O/P : FULL LOAD Ta : 25°C Tc34 : 52.5°C Life: 45737 hrs I/P : 48VDC O/P : FULL LOAD Ta : 53.4°C Tc34 : 74.1°C Life: 10234 hrs</p>		P																												
19	CRITICAL COMPONENT RECORD (FOR QC INSPECTION REFERENCE ONLY)	<p>A: FUSE : 3A/250V INPUT DIODE : 1N5401 LINE FILTER : LS TF-096C EE-25 TRANSFOMER : TF-327 EER-28 POWER SWITCHER : K891 OUTPUT DIODE : D83-004 OUTPUT CAPACITOR : 2200uF/16V(v) 105°C HL INPUT CAPACITOR : 220uF/100V(v) 105°C HL P.C.B : SD-50 FR-4 2 OZ DS</p>																														
DATE	SAMPLE	TEST RESULT	TEST	APPROVAL																												
980421	SD-50C	PASS	H.C.LIOU	Max Lin																												