



Test Report : SKMW30G-03

30W 1"x1" Package DC-DC Regulated Converter

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Control Function Test

■ SAFETY TEST

Safety Test

■ RELIABILITY TEST

Environment Test

DESIGN VERIFY TEST
OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	VOLTAGE ACCURACY	-1.5 % ~ +1.5 % (Max)	I/P:48VDC O/P:FULL LOAD Ta:25°C	+0.64 %	P
2	RIPPLE & NOISE	75 mVp-p (Max)	I/P:48VDC O/P:FULL LOAD Ta:25°C	34 mV	P
3	LINE REGULATION	-0.2% ~ +0.2% (Max)	I/P:18VDC~75VDC O/P:FULL LOAD Ta:25°C	-0.012% ~ +0.001%	P
4	LOAD REGULATION	-0.2% ~ +0.2% (Max)	I/P:48VDC O/P:NO LOAD-FULL LOAD Ta:25°C	-0.06 % ~ +0.06 %	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	EFFICIENCY	88 % (Typ)	I/P:48VDC O/P:FULL LOAD Ta:25°C	88.4 %	P
2	DC CURRENT	590 mA / FULL LOAD (Max) 8 mA / NO LOAD (Max)	I/P:48VDC O/P:NO / FULL LOAD Ta:25°C	587 mA / FULL LOAD 5 mA / NO LOAD	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	110%~170% LOAD (Typ)	I/P:48VDC O/P:TESTING Ta:25°C	152.96 %	P
2	INPUT UNDER VOLTAGE LOCKOUT	Power Up 17V (Typ) Power Down 16V (Typ)	I/P:TESTING O/P: 10% LOAD Ta:25°C	Vin turn off : 16.12V Vin turn on : 16.90V	P
3	SHORT PROTECTION	CONTINUOUS	I/P:75VDC O/P:FULL LOAD Ta:25°C	NO DAMAGE OK	P

CONTROL FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	REMOTE CONTROL	Power on : R.C >3.5Vdc~75Vdc or open Power off : R.C <1.2Vdc or short	I/P:48VDC O/P:10% LOAD Ta:25°C	OK	P

2	TRIM CONTROL	+10%~ -10% (Typ) Trim ~ +Vout Trim DOWN Trim ~ -Vout Trim UP Using 10k ohm VR	I/P:48VDC O/P:10% LOAD Ta:25°C	Trim DOWN -10.63 % Trim UP +9.90 %	P
---	--------------	--	--------------------------------------	---------------------------------------	---

SAFETY TEST

SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P:1500 VDC/min	I/P-O/P:1500 VDC/min Ta:25°C	I/P-O/P: 0.002mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P:500 VDC Ta:25°C	I/P-O/P>100MΩ NO DAMAGE	P

RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT								
1	TEMPERATURE RISE TEST	1. ROOM AMBIENT BURN-IN : 12HRS I/P:48VDC O/P:FULL LOAD Ta=25°C 2. HIGH AMBIENT BURN-IN : 12HRS I/P:48VDC O/P:FULL LOAD Ta=61°C			P								
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>1</th> <th>2</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>CASE</td> <td>41.8°C</td> <td>76.6°C</td> </tr> </tbody> </table>		NO	Position	1	2	1	CASE	41.8°C	76.6°C		
NO	Position	1	2										
1	CASE	41.8°C	76.6°C										
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOURS	I/P:48VDC O/P: FULL LOAD Ta= -40°C	TEST : OK	P								

OTHER

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	MTBF	MIL-HDBK-217F,GB,25°C,Full Load TOTAL FAILURE RATE : 1.081 M.T.B.F : 925,252 HRS			P

TEST RESULT	TESTER	APPROVAL
PASS	ALROY WANG	VINCNET ZENG