



Test Report : SPA01A-05

1W DC-DC Regulated Single Output Converter

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

■ SAFETY TEST

Safety Test

■ RELIABILITY TEST

Other

DESIGN VERIFY TEST
OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	VOLTAGE ACCURACY	-2 % ~ +2 % (Max)	I/P:12VDC O/P:FULL LOAD Ta:25°C	-0.54 %	P
2	RIPPLE & NOISE	60 mVp-p (Max)	I/P:12VDC O/P:FULL LOAD Ta:25°C	15 mV	P
3	LINE REGULATION	-0.5 % ~ +0.5 % (Max)	I/P:9VDC~18VDC O/P:FULL LOAD Ta:25°C	-0.12 % ~ +0 %	P
4	LOAD REGULATION	-0.5 % ~ +0.5 % (Max)	I/P:12VDC O/P:MIN-FULL LOAD Ta:25°C	-0 % ~ +0.05 %	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	9VDC~18VDC	I/P:TESTING O/P:FULL LOAD Ta:25°C	7.64 ~ 18VDC	P
2	EFFICIENCY	77 % (Typ)	I/P:12VDC O/P:FULL LOAD Ta:25°C	78.11 %	P
3	DC CURRENT	110 mA / FULL LOAD (Max) 20 mA / NO LOAD (Max)	I/P:12VDC O/P:NO / FULL LOAD Ta:25°C	106.6 mA / FULL LOAD 13.9 mA / NO LOAD	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	130%~200 % (Typ)	I/P:12VDC O/P:TESTING Ta:25°C	164 % HICCUP MODE AUTO-RECOVER	P
2	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P:18VDC O/P:FULL LOAD Ta:25°C	NO DAMAGE HICCUP MODE AUTO-RECOVER	P

SAFETY TEST
SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P:1500 VDC/min	I/P-O/P:1500 VDC/min Ta:25°C	I/P-O/P: 0.02mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P:500 VDC Ta:25°C	I/P-O/P>100MΩ NO DAMAGE	P

RELIABILITY TEST
OTHER

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	MTBF	MIL-KDBK-217F NOTICES 2 PARTS COUNT TOTAL FAILURE RATE : 1.91624 M.T.B.F : 521855 HRS			P

TEST RESULT	TESTER	APPROVAL
PASS	PETER CHENG	VINCENT TSENG